Stock Class

- 1. Only a factory skid plate is a allowed.
- 2. Doors must be chained, strapped, or welded shut! If they open you're not racing!
- 3. The hood and trunk must be chained shut!
- 4. May run any Dot. **No** mud, cut or altering of tires allowed!
- 5. Any year 4 cyl or 6 cyl front wheel drive is allowed.
- 6. Drivers door may be welded only. Padding on the inside is ok also.
- 7. Drivers door protection is recommended. You can put a steel plate inside the door or add a grinder blade to the outside of the door. **No** sharp edges and bolts must not stick out either!
- 8. The gas tank may remain in stock position as long as it is in front of the rear axel.
- A battery can also remain in the stock location, but must be securely fastened. If moved to the
 drivers compartment then it must be secure and covered! Only exception is a dry gel doesn't
 need to be covered.
- 10. Rear ends must be stock in the stock location with **NO** altering.
- 11. Frames must be stock **No** welding or altering.
- 12. Engine must be stock and to the model of the vehicle.
- 13. Transmission must be to the vehicle also. No changing!!
- 14. Ecm maybe relocated and foamed in.
- 15. Engine and Transmission may be chained, but if the official believes it is excessive you will not race.
- 16. All plastic, bumper covers and lights must be removed!
- 17. Any part of the body that needs replaced may be done with the same gauge or thickness of stock.
- 18. Bumpers may be replaced another but can't be stronger than the original. No sharp ends and has to be bolted and not welded.
- 19. Posts behind the driver for a roll over and a support from side to side must be added.
- 20. There is no gray areas!!! All rules will be interpreted by the officials and their decision on them will be final.